

welding equipments

gas welding equipments

fabrication machineries

fume extr

gas manifi

complete

welding training and qualifying facility



Your Reliable Alternative

PLASMA CUTTING

LG-30/60E



**INVERTER PLASMA
 TOUCH CUT**
 240V/1Ph/50Hz
 15~30/20~60A
 60A @ 60%
 8/25mm cut
 16/30kg

Order No : MC6002/MC6004

LG-100/200E

**INVERTER PLASMA
 TOUCH CUT**
 415V/3Ph/50Hz
 20~100/40~200A
 100A @ 60%
 35/65mm cut
 43/68kg

Order No :
MC6005/MC6008

SPOT WELD



DN-5

SPOT WELD
 240/380V/1/3Ph/50Hz
 5KVA
 20%
 60kg

DN-16

SPOT WELD
 415V/3Ph/50Hz
 16KVA
 20%
 100kg

DN-25

SPOT WELD
 415V/3Ph/50Hz
 25KVA
 20%
 130kg



Model	MZ-3C
Seeding Wire Speed	20-200 cm/min
Sending Wire Mode	Changing Speed / Constant Speed
Welding Speed	15-150 cm/min
Welding Head Adjust Range (Plumb)	95mm
Welding Head Adjust Range (Horizontal)	± 35mm
The Stub Up / Down Range	100 mm
Welding Head Angle Of Deflection (Left-Right)	45°
Welding Head Angle Of Deflection (Front-Rear)	60°
Dimension (mm)	920 x 455 x 820
Weight (kg)	52

